



**PATENT** Attorney Docket No. 40725.830063.000 Express Mail No. EL415726373US

#### IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of	)
JORMA ANTERO SEPPANEN	) )
	) Group Art Unit:
Serial No. 09/454,124	)
Filed: December 3, 1999	Examiner:    OFFINED
For: SIGNAL QUALITY	MAR 2 9 202
INDICATOR APPARATUS AND	$GRO_{G} = GRO_{G}$
METHOD PARTICULARLY	) "NOUP 2700
USEFUL FOR MOBILE	)
TELEPHONES	)
	)

### CERTIFICATE OF MAILING BY EXPRESS MAIL

Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

The undersigned hereby certifies that the attached Preliminary Amendment, return card and this Certificate of Mailing by Express Mail, relating to the above application, were deposited as "Express Mail" Mailing Label No. EL415726373US, with the United States Postal Service, addressed to the Assistant Commissioner for Patents, Washington, D.C., 20231, on February 17, 2000.

17 FEBRUARY 2000

Date

Earl C. Hancock, Reg. No. 19,472

**HOLLAND & HART LLP** 555 17th St., Suite 3200

P.O. Box 8749

Denver, Colorado 80201

(303) 473-2708

2626270\_1.DOC



Attorney Docket No. 40725.830063.00

Express Mail No. EL415726373US

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of	)
JORMA ANTERO SEPPANEN	)
0 113 00/454 104	) Group Art Unit:
Serial No. 09/454,124	) Examiner:
Filed: December 3, 1999	
For: SIGNAL QUALITY INDICATOR APPARATUS AND	) MAR 2 9 2000
METHOD PARTICULARLY USEFUL FOR MOBILE TELEPHONES	GROUP 2700
	)

## PRELIMINARY AMENDMENT

Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

Please amend the above-identified patent application as follows:

# In the Specification:

Page 7, lines 8-10, delete "The signal is received at 47 as enabled by detector 48. It is compared against a predetermined level and either a good, or a not-good output is produced." and insert: - The current signal quality indicator status is determined in block 64, that is if the signal is currently displayed as "good" or "not good". Depending on the status, the decision goes to block 65 or 66, respectively.

Page 8, line 1, delete "whether".

Page 8, lines 2 through 8, delete everything between "audio distortion is above--" and "---unacceptable amount of distortion." and insert --currently displayed audio quality indicator, that is, if the signal

A

A Cont.